

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/113112 A1

(51) International Patent Classification⁷: **B60K 41/00**, 6/02

(21) International Application Number:

PCT/JP2004/008686

(22) International Filing Date: 15 June 2004 (15.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-178730 23 June 2003 (23.06.2003) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **IIDA, Hiroaki** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP). **ITANO, Hideo** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP).

(74) Agent: **ITEC INTERNATIONAL PATENT FIRM**; Pola-Nagoya Bldg., 9-26, Sakae 2-chome, Naka-ku, Nagoya-shi, Aichi 4600008 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: **HYBRID VEHICLE AND METHOD OF CONTROLLING THE SAME**



(57) Abstract: In a constant speed drive (in an auto cruise), the procedure of the invention executes proportional control to set an accelerator opening Acc corresponding to an observed vehicle speed and a target vehicle speed. When the accelerator opening Acc is less than a preset opening A2 included in a dead zone where a torque demand Tr* is kept equal to 0, the procedure corrects the accelerator opening Acc to have a corresponding torque demand Tr* included in a negative zone where the torque demand Tr* takes negative values and linearly increases. This arrangement heightens the linearity of the graph of the torque demand Tr* against the accelerator opening Acc in the constant speed drive, compared with the linearity in a standard drive.

WO 2004/113112 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.